



GALAXY  
EARTHMOVER &  
MINING

TRA: E-3/L-3  
Speed Rating: B

LDSR 300 is specially constructed for wheel loaders operating in the toughest environments. Transportation of heavy load demands excellent stability and robustness. Sturdy radial construction coupled with strong sidewall protector provides LDSR 300 superior strength and endurance to withstand challenging terrains. Premium tread compounds provide excellent protection against lug-tearing and chunking, helping the machine to perform efficiently without any downtime shaped tread pattern with stepped lugs ensure optimal traction and enhanced self cleaning assuring high productivity.

Articulated Dump Trucks - 17.5R25

Size	Pattern	Rim	Unloaded		Static Loaded Radius mm	Static Loaded Width mm	Rolling Circumference mm	NSD mm	TKPH/ TMPH	Load Index Speed Symbols	MAX SPEED	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES											
			Dimension									Star Mark										**	
												OD mm	SW mm	KPA	275	300	325	350	375	400	425	450	475
17.5R25	LDSR 300	14.00/1.5 X 25	1350	445	623	0	4009	28.9	0	167B	50 KMPH	Kg	3350	3550	3750	4000	4125	4375	4625	4750	5000	5150	5450

E-Marking Number:

