



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **A8**

FarmPRO 85 series of agricultural radial tires have multi angle lug design with steep angles at the center that enables smooth ride along with self cleaning characteristics. The shallow angle at shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead to bead distance to facilitate perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall.

TRACTOR - 340/85R36

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
		Tractor Application												
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	
340/85R36(13.6R36)	W12 X 36 W11 X 36	353	1492	689	4335	132A8 132B	0.8	2880	1880	1390	1340	1250	1250	
							1.2	3800	2480	1830	1770	1650	1650	
							1.4	4140	2700	2000	1930	1800	1800	
							1.6	4600	3000	2220	2140	2000	2000	
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
		Tractor Application												
									10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
340/85R36(13.6R36)	W12 X 36 W11 X 36	353	1492	689	4335	132D	0.8	1880	1480	1440	1370	1315	1250	2880
							1.2	2480	1960	1900	1810	1735	1650	3800
							1.4	2700	2135	2070	1970	1890	1800	4140
							1.6	3000	2370	2300	2190	2100	2000	4600

*Alliance allows for free rolling application:Load capacity to be increased by 20%,after increasing the inflation pressure by 20%

