



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **D**

Agri-star 385 Radial tire is a part of the 85 Series and represents our focus on developing tires that meet the demands of extensive developments in the tractor industry. The tread-pattern is designed with specific lug construction and strength required for modern high HP/ speed tractors. Special focus is given to the flexibility characteristics of the tire. The 385 promises a smooth and comfortable ride. Strong textile casing combined with high quality tread and sidewall rubber compounding ensures better tire life.

TRACTOR RADIAL HIGH SPEED - 460/85R34

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
								Speed									
								Field operation			Not high and sustained torque; Road transport						
		High Tor	Low Torque														
SW mm	OD mm	10 kmph	10 kmph	20 kmph	Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph						
460/85R34	W16L, W15L, W14L	486	1653	749	4893	144D 147A8	0.8	2190	2870	2460	4300	2810	2220	2150	2050	1960	1870
							1	2490	3260	2800	4900	3200	2520	2450	2330	2240	2130
							1.3	2910	3810	3260	5700	3720	2940	2850	2720	2600	2480
							1.6	3280	4300	3680	6440	4200	3320	3220	3070	2940	2800

The Size 460/85R34 (LI - 147A8/144D(*)) is no longer active for production

