



ALLIANCE
EARTHMOVER &
MINING

TRA: **NA**
Speed Rating: **D**

The Alliance 212 D.S. Logger is an ideal design (in Earthmoving and Loaders) for heavy-duty jobs under all working conditions. Its special non-directional tread design and heavy-duty all nylon carcass results in a strong tire that withstand cuts, snags and bruises under all service conditions.

TRANSPORT - 13.00-25

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		SW mm	OD mm					Speed								
								15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	50 kmph	55 kmph	60 kmph	65 kmph
13.00-25	10 8.5	651	1285	582	3800	16PR	2.5	3020	2970	2920	2860	2780	2700	2650	2510	2300
							2.75	3190	3140	3080	3020	2940	2850	2790	2650	2420
							3	3360	3300	3240	3180	3090	3000	2940	2790	2550
						152B 146D	3.25	3520	3450	3390	3330	3230	3140	3080	2920	2670
							3.5	3670	3610	3540	3480	3380	3280	3210	3050	2790
							3.75	3830	3760	3690	3630	3520	3420	3350	3180	2910
							4	3980	3910	3830	3760	3660	3550	3480	3300	3000
						18PR	4.25	4070	3990	3920	3850	3740	3630	3560	3380	3090
						154B 149D	4.5	4200	4130	4050	3980	3860	3750	3680	3490	3250
							20PR	4.75	4350	4270	4190	4110	4000	3880	3800	3610
						156B 151D	5	4480	4400	4320	4240	4120	4000	3920	3720	3450

Note : For above mentioned size only 16 PR is active for production.

