



ALLIANCE  
LAWN GARDEN & TURF

TRA: **HF-1**  
Speed Rating: **B**

Alliance 322 tread pattern provides extremely gentle operation of golf carts, turf equipment and lawn mowers. The high void to rubber ratio enables long tread life, large footprint, as well as low and uniform ground pressure. Low tread depth and unique shoulder design minimize turf damage on hills and during sharp turns. The large footprint allows more tread on the ground and keeps the machine/equipment from sinking in while crossing wet or soft ground. The 322 tread pattern also provides smooth operation on hard surfaces.

IMPLEMENT - 41X14.00-20 NHS

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
								Mixed application				
		SW mm	OD mm					Static kmph	10 kmph	15 kmph	30 kmph	50 kmph
41X14.00-20	11	381	1092	493	3224	4PR	1.2	2460	1800	1500	1280	1140
						120B	1.5	2810	2050	1720	1460	1300
							1.7	3020	2210	1850	1570	1400
						6PR	1.9	3220	2350	1970	1670	1490
						127B	2.2	3500	2560	2140	1810	1620
							2.5	3780	2770	2310	1960	1750

Note: For abovementioned size 4 PR is no longer active for production.

