



ALLIANCE
AGRICULTURE

TRA: **R-1W+**
Speed Rating: **A6**

Multi angled tread pattern for on/off road suitability. Stepped lugs help in improving traction. Superior tread compound and wide nose bar gives more life on the road. The tire features high NSD for improved traction. Shadow tie bar adds strength to the lugs.

TRACTOR - 18.4-38

| Size | Rim | Unloaded Dimension | | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Recommended Load | | | | |
|---------|-----|-------------------------|---------|-------------------------|--------------------------|-----------------------|------------------------|------------------|---------|---------|------|------|
| | | | | | | | | Speed | | | | |
| | | Drive Wheel Application | | | | | | | | | | |
| | | Static kmph | 10 kmph | | | | | 20 kmph | 25 kmph | 30 kmph | | |
| 18.4-38 | 16 | 467 | 1755 | 799 | 5121 | 8 | 0.8 | 4390 | 2670 | 2290 | 2040 | 1910 |
| | | | | | | 142A6 | 1.2 | 5570 | 3390 | 2900 | 2590 | 2420 |
| | | | | | | | 1.4 | 6100 | 3710 | 3180 | 2840 | 2650 |

