



GALAXY
AGRICULTURE

TRA:
Speed Rating: **D**

Galaxy Flotstar is the latest offering in the Radial Flotation Segment. Designed with a unique Non directional tread design that provides superior Traction and mobility in both field and on road and enables self cleaning. Has a steelbelted construction that prevents damages and ensures long life, uniform footprint ensuring better soil protection.

Agri Transport - 560/45R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Mixed applications							
		SW mm	OD mm					Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph	65 kmph	70 kmph
560/45R22.5	AG16.00 X 22.5	544	1076	483	3303	152D⊕	0.8	2645	2070	1898	1737	1564	1392	1150	1047
							1.2	3680	2880	2640	2416	2176	1936	1600	1456
							1.6	4140	3240	2970	2718	2448	2178	1800	1638
							2.4	5428	4248	3894	3564	3210	2856	2360	2148
							3.2	6900	5400	4950	4530	4080	3630	3000	2730
							4	8165	6390	5858	5361	4828	4296	3550	3231

