



ALLIANCE
AGRICULTURE

TRA:
Speed Rating: **D**

Agriflex+ 881 is the latest addition to Alliance engineered series of Agriflex tires. Specially designed to provide higher load carrying capacities for Planters, balers, trailers and agricultural implements. It can carry upto 40% more load at the same amount of pressure while ensuring minimum soil compaction. Robust all steel construction with presence of stubble guard compound assures minimum downtime and maximum vehicle productivity making it an ideal partner for heavy duty agriculture applications.

IMPLEMENT - VF 445/65R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
		SW mm	OD mm					Speed							
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph
VF 445/65R22.5	14	444	1150	501	3450	176D	0.8	3910	1870	1770	1730	1700	1700	1700	1700
							1.2	5010	2400	2270	2220	2180	2180	2180	2180
							1.6	6100	2920	2760	2700	2650	2650	2650	2650
							2.4	8170	3910	3690	3620	3550	3550	3550	3550
							3.2	10060	4810	4550	4460	4375	4375	4375	4375
							4	12190	5830	5510	5410	5300	5300	5300	5300
							5.4	16330	7810	7380	7240	7100	7100	7100	7100

