https://yokohama-atg.com Generated on: 17 May, 2024



ALLIANCE **AGRICULTURE**

TRA: Speed Rating: **D** Alliance Agriflex+ 389 VF introduces the next round of innovation: the world's first VF flotation tire offers the possibility to be operated at 30% lower inflation pressure as a conventional flotation tire. With Agriflex+ 389 we have trailer tires which allow to mirror the pressure of VF tires on today's high horsepower tractors. This significantly reduces the footprint pressure and thus results in low soil compaction.

Fronts & Implements - VF500/60R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Mixed Application							
		SW mm	OD mm					Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph
VF500/60R22.5	AG16.00X22.5	503	1172	517	3536	157D	1.2	4960	3990	3690	3430	3130	2840	2580	2430
							1.6	6120	4920	4560	4230	3870	3510	3180	3000
							2	6430	5170	4790	4440	4060	3690	3340	3150
							2.4	7240	5820	5400	5010	4580	4150	3760	3550
							2.8	8420	6770	6270	5820	5320	4830	4370	4125

