



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **D**

AGRISTAR 375 VF is ideal for applications on combine harvesters. The tread pattern and lugs are designed to enable a comfortable and smooth ride on hard surfaces, combined with high traction and excellent self cleaning abilities off-road. Durable and elastic sidewalls contribute to a long tire life. A special stubble guard tread rubber compound contributes to long and efficient work on harvesters.

Harvester - VF 800/65R32

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
								Not high and sustained torque; Road transport					CFO	
		10 kmph	15 kmph					20 kmph	60 kmph	70 kmph	15 kmph	30 kmph		
VF 800/65R32	DW27 X 32	800	1853	807	5531	181D	0.8	5220	4875	4875	4875	4440	7556	6337
							1	5840	5450	5450	5450	4960	8447	7085
							1.2	6430	6000	6000	6000	5460	9300	7800
							1.6	7820	7300	7300	7300	6640	11315	9490
							2	8840	8250	8250	8250	7510	12787	10725

From 15Kmph-60Kmph, the Load will remain same for the Respective Inflation Pressure. For Non-Cyclic Application only.

