



PRIMEX
**EARTHMOVER &
MINING**

TRA: **HF-1**
Speed Rating: **B**

Primex Geomaster is designed specifically for the exploration and geophysics industries. The large area of this tire provides superior buoyancy and reduces ground disturbance and soil compaction

Geoseismic Vehicle - 66X44.00-25NHS



Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
								Speed					
		SEISMIC VEHICLES						15 kmph	50 kmph				
		SW mm	OD mm										
66X44.00-25NHS	36HFX25	1100	1722	752	4845	6 151B 160A3	1.03	4500	3450				

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
								Speed					
		SEISMIC VEHICLES						15 kmph	50 kmph				
		SW mm	OD mm										
66X44.00-25	36HFX25	1100	1722	752	4845	20 176B 185A3	3.4	9250	7100				

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
								Speed					
		SEISMIC VEHICLES						15 kmph	50 kmph				
		SW mm	OD mm										
66X44.00-25	36HFX25	1100	1722	752	4845	26 181B 191A3	4.5	10900	8250				