



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: **R-3**
Speed Rating: **A8**

The Alliance 329 is a diamond tread design tire built with a strong nylon construction. Its wide and extended tread protects shoulders and sidewalls against cutting and side snagging. The special cut and chip resistant compound ,heat resistant compound and the tires strong nylon construction provide long life to the tire.

TRACTOR - 14.9-24

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
								Speed								
								Field operation			Not high and sustained torque; Road transport					
								High Tor	Low Torque							
		10 kmph	10 kmph					20 kmph	Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph		
14.9-24	W13 W12	394	1241	569	3698	6PR	1	1370	1790	1540	2940	1920	1420	1370	1280	1160
						123A8	1.2	1520	1990	1700	3270	2130	1580	1520	1420	1290
							1.4	1660	2170	1860	3570	2330	1720	1660	1550	1410
						8PR	1.5	1730	2270	1940	3730	2430	1800	1730	1620	1470
						128A8	1.6	1800	2350	2020	3860	2520	1860	1800	1680	1530
							1.8	1930	2520	2160	4140	2700	2000	1930	1800	1640

Recommended rim in red (Bold)

