



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: R-4
Speed Rating: D

Alliance 606 tire for Loaders and Dozers is a low section tire for light earthmoving equipment. The tire is an all steel radial tire with steel belted construction. The unique non-directional tread design suits on/off road services. High mileage, easy self cleaning, best traction, fuel saving and ride comfort are some of its advantages.

EM - 365/70R18

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Off-the road			
		Static kmph	5 kmph					10 kmph	25 kmph		
365/70R18	11 13	400	1000	440	2902	146A2	2.25	3570	2520	2230	1900
							2.5	3790	2680	2370	2010
							2.75	4000	2830	2500	2130
							3	4210	2970	2630	2240
							3.25	4420	3120	2760	2350
							3.5	4610	3250	2880	2450
							3.75	4800	3390	3000	2550
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		Static kmph	5 kmph					10 kmph	25 kmph		
365/70R18	11 13	400	1000	440	2902	146A2	2.7	4010	3230	3010	2790
							3	4270	3440	3200	2960
							3.3	4500	3630	3380	3130
							3.6	4730	3810	3550	3290
							3.9	4970	4000	3730	3450
							4.2	5180	4180	3890	3600
							4.5	5400	4350	4050	3750

Recommended rim in red

