



ALLIANCE
EARTHMOVER &
MINING

TRA: G-2/L-2
Speed Rating: B

The Alliance 306 design is a tough road grader tire developed especially to withstand rugged terrains. Its massive lugs are reinforced and connected to an extra thick center tread rubber belt. This design feature enables the tire to be used for long lasting service in tough conditions. The nylon construction enables the tire to overcome obstacles and provides a longer wearing period.

TRANSPORT - 17.5-25 L-2

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		SW mm	OD mm					Speed								
								15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph
17.5-25 E-2	14* 14.00SDC	444	1348	599	3940	12PR	1.5	3230	3170	3110	3050	3000	2970	2940	2880	2790
							1.75	3530	3470	3400	3340	3280	3240	3210	3150	3060
						153B	2	3820	3750	3680	3610	3550	3510	3480	3410	3310
							2.25	4090	4020	3940	3870	3800	3760	3720	3650	3540
						16PR	2.4	4180	4100	4030	3950	3880	3840	3800	3730	3620
							2.6	4380	4300	4220	4140	4070	4030	3990	3910	3790
						158B	2.8	4570	4490	4410	4320	4240	4200	4160	4080	3960
							3	4760	4680	4590	4510	4420	4380	4340	4250	4120
						20PR	3.25	4960	4870	4780	4700	4610	4560	4520	4430	4300
							3.5	5170	5080	4990	4900	4800	4760	4710	4620	4480
						164B	3.75	5390	5290	5190	5100	5000	4950	4910	4810	4670
							4	5600	5500	5400	5300	5200	5150	5100	5000	4850

