



ALLIANCE  
AGRICULTURE

TRA: **F-2**  
Speed Rating: **A8**

Alliance 313 tire is a multipurpose low-section steering wheel tire for heavy duty tractors. It provides high mileage on road and industrial applications. It has a strong nylon construction and uses high grade compounds which guarantee long tire life.

TRACTOR - 14L-16.1SL

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph
14L-16.1SL	W11C	346	986	450	2930	6PR	1.5	1950	1680	1510	1290	1120	1010	900
						117A6 109A8	1.7	2090	1800	1620	1380	1200	1080	960
							1.9	2230	1930	1730	1480	1285	1160	1030
						8PR	2	2370	2040	1840	1560	1360	1220	1090
						123A6 116A8	2.2	2500	2160	1940	1660	1440	1300	1150
							2.5	2700	2330	2090	1780	1550	1400	1240
						10PR	2.6	2800	2420	2170	1850	1610	1450	1290
						127A6 120A8	2.7	2880	2480	2230	1900	1650	1490	1320
							3	3040	2630	2360	2010	1750	1580	1400

Highlighted column indicates 1) 6PR and above with a 25% increase in inflation pressure 2) In case where front-end loader is fitted on the tractor, =100% applies.

