



ALLIANCE  
EARTHMOVER &  
MINING

TRA: G-2/L-2  
Speed Rating: A8

Alliance 307 is a pattern developed for Grader-Loader applications. The design provides optimal traction and cut resistance and also enables the tire to have excellent self cleaning characteristics and long life.

Bias Ply Loader Grader L-2/G-2 - 14.00-24

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
								Speed	
		SW mm	OD mm					Recommended Load Capacity (For Grader)	Recommended Load Capacity (For Loader/Dozer/TH)
								40 kmph	10 kmph
14.00-24	8.00TG	360	1338	607	3910	12PR	2.5	3075	NA
							4.25	NA	6300
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
								Speed	
		SW mm	OD mm					Recommended Load Capacity (For Grader)	Recommended Load Capacity (For Loader/Dozer/TH)
								40 kmph	10 kmph
14.00-24	8.00TG	360	1338	607	3910	16PR	3.25	3650	NA
							5.5	NA	7300

