



PRIMEX  
FORESTRY

TRA: **HF-4**  
Speed Rating: **B**

Primex Logstomper Xtreme Flotation TS features a variable angle lug design that is tapered from the center to the shoulder. This delivers excellent hillside stability, superior traction and exceptional performance in varied ground conditions. The Logstomper Xtreme Flotation TS is engineered with a highly cut and chip resistant compound as well as heavy sidewall and under tread gauges for added protection in demanding service.

AGRICULTURAL LOADER - 66X43.00-26

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
								High floatation & Forestry Logging				
		SW mm	OD mm					Static kmph	10 kmph	15 kmph	30 kmph	50 kmph
66X43.00-26	DW36B	1054	1747	767	5066	20PR	2	9740	7690	6430	5450	4870
						174B	2.5	11100	8770	7330	6220	5550
							3	12340	9750	8140	6910	6170
							3.45	13400	10590	8840	7500	6700

\* Alliance allows for free rolling application: Load capacity to be increased by 20%, after increasing the inflation pressure by 20%. Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

