



ALLIANCE  
AGRICULTURE  
  
TRA: I-3  
Speed Rating: B

Alliance 331 Radial is a traction pattern with good self-cleaning characteristics. It is suitable for on/off road agricultural service on tractors, cross country vehicles, trailers and agricultural implements. High load carrying capacity and low inflation pressure are the main characteristics of this tire. A strong construction with steel belts ensure long life and superior performance for the required application.

IMPLEMENT - 600/45R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
								Speed					
								Mixed application					
		SW mm	OD mm					Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph
600/45R22.5	20 AG20.00	608	1152	511	3502	165A8 161B	0.8	4700	2800	2380	2240	2000	1800
							1	5360	3190	2710	2550	2280	2050
							1.2	5970	3560	3020	2840	2540	2290
							1.5	6820	4060	3450	3250	2900	2610
							1.6	7070	4210	3580	3370	3010	2710
							2	8060	4800	4080	3840	3430	3090
							2.2	8530	5080	4320	4070	3630	3270
							2.4	8980	5350	4550	4280	3820	3440
							2.8	9820	5850	4970	4680	4180	3760
							3.2	10620	6330	5380	5060	4520	4070
							3.6	11370	6780	5760	5420	4840	4360
							4	12100	7210	6130	5770	5150	4640

When used in RDT, ADT or construction applications, the applicable warranty will be as per Earth Moving/ Construction application's warranty policy.

