



ALLIANCE  
FORESTRY

TRA: **LS-2**  
Speed Rating: **A8**

FORESTAR 346 Forestry Flotation is a bias belted tire with steel reinforcement for high puncture resistance. The tire has a special tread compound and has very thick sidewalls and under tread. The reinforced bead of the tire provides exceptional performance. Its lower lug angle provides excellent grip and exhibits self cleaning characteristics due to its wide inter-lug space which is vital in logging applications. The close spacing of the lugs in the centre of the tire reduces rolling resistance on hard surfaces. The 346 is designed to handle various terrains without chains/ bogie trucks.

FORESTRY - 600/65-34

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
								Recommended load, kg (lbs)						
								Drive wheel					Forestry use	
		Static kmph	10 kmph					20 kmph	30 kmph	40 kmph	10*HT kmph	10*LT kmph		
600/65-34	DW20A	600	1640	762	4927	14PR	1.6	7480	4550	4000	3480	3250	3250	4000
							1.8	8030	4890	4290	3730	3490	3490	4290
						157A8 164A2	2	8530	5190	4560	3970	3710	3710	4560
							2.2	9020	5490	4820	4190	3920	3920	4820
							2.4	9490	5780	5070	4410	4125	4125	5070
						16PR	4	9660	5880	5170	4490	4200	4200	5170
						160A8 167A2	4.5	10350	6300	5540	4820	4500	4500	5450

