



ALLIANCE  
CONSTRUCTION &  
INDUSTRIAL

TRA: E-2  
Speed Rating: B

The tread pattern of 225 MPT is designed for self-cleaning as well as for smooth on road driving. The diagonal lug design of the tire provides best traction in all services, terrain and weather conditions besides improving resistance to side slips. Its wide based design provides high flotation properties and permits low inflation pressure. For free rolling and better mileage on road service, it is recommended to mount tires in opposite direction than usual.

EXCAVATOR - 10.00-20ML

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
								Speed	
		SW mm	OD mm					50 kmph	
10.00-20ML	7.5 X 20	275	1065	500	3267	16 148B	7.9	3150	

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								speed							
		SW mm	OD mm					Static kmph	10 kmph	20 kmph	25 kmph	30 kmph	40 kmph	45 kmph	50 kmph
10.00-20ML	7.5 X 20	275	1065	505	3240	14	5.5	5240	3060	2950	2900	2870	2770	2660	2610
						145B 143B		5500	3210	3100	3040	3010	2900	2790	2740
								6.6	5830	3400	3290	3230	3200	3080	2900

Note : For above mentioned size 12 PR is no longer active for production.

