



ALLIANCE  
AGRICULTURE  
  
TRA: **R-1**  
Speed Rating: **A8**

Alliance 768 Value Plus is specially designed to meet the unique demands of pivot irrigation. Built with strong nylon carcass construction which enhances its ability to carry continuous heavy loads. Designed with low lug angles and rounded shoulders for optimal traction and maximum crop protection. The presence of special ozone compound protects it from cracking ensuring excellent durability.

TRACTOR - 11.2-24

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load											
								Speed											
								Tractor Application											
		Static kmph	5 kmph					10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph			
11.2-24	W10X24, W9X24	280	1100	493	3250	6 110A8	0.8	1520	1120	990	880	810	730	710	680	660	630	600	
							1.2	2070	1430	1260	1130	1030	930	900	870	840	810	760	
							1.4	2250	1560	1380	1230	1130	1020	980	950	920	880	840	
							1.6	2280	1680	1490	1330	1220	1100	1060	1020	990	950	900	
							1.8	2600	1800	1590	1420	1300	1180	1130	1090	1060	1020	960	

