



GALAXY
CONSTRUCTION &
INDUSTRIAL

TRA: **R-1**
Speed Rating: **A8**

The Galaxy HIGH-LIFT RADAIL R-1, is an ideal radial tire for off-the-road and agricultural services. The tire is engineered with radial textile-carcass and polyester belt. Specific tread pattern enables wide range of applications, including construction machinery, as well as agro-industrial mechanizations, such as backhoe loaders and telescopic handlers.

Telehandler - 500/70R24IND(19.5LR24IND)

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
								Speed								
		Constant Load						Cyclic Application								
		Static kmph	10 kmph					30 kmph	40 kmph	50 kmph	10 kmph	30 kmph	40 kmph	50 kmph		
500/70R24IND(19.5LR24IND)	W16L X 24	503	1310	596	3965	164A8	3	9710	5280	4520	4220	3840	6330	4520	4220	3840
	W15L X 24						3.5	10630	5780	4940	4620	4200	6930	4940	4620	4200
	W16A X 24						4	11500	6250	5350	5000	4550	7500	5350	5000	4550
	DW16A X 24															

