



GALAXY
AGRICULTURE

TRA: **R-1**
Speed Rating: **A6**

EarthPRO 348 has a modern curved design developed mainly for the heavy duty agricultural segment. The multi angled lug design enables smooth riding on the road and displays excellent traction during field operations. The special stepped surfaces between lugs enable the tire to have excellent self cleaning characteristics. The special tread compound provides protection against cuts and cracks.

TRACTOR DIAGONAL - 16.9-30

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Tractor application							
		SW mm	OD mm					Static kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph
16.9-30	W15L X 30	429	1485	667	4370	12	0.8	3400	2070	1920	1780	1580	1480	1410	1330
	DW15A X 30						1.2	4300	2620	2430	2240	2000	1870	1780	1680
	W14L X 30					144A6	1.6	5080	3090	2870	2650	2360	2210	2100	1990
	DW14A X 30						2	5800	3530	3280	3020	2700	2520	2390	2270
	X 30						2.4	6440	3920	3640	3360	3000	2800	2660	2520

