



ALLIANCE  
FORESTRY  
  
TRA: **LS-2**  
Speed Rating: **A8**

Alliance 643 Forestar III is engineered for ultimate track compatibility. Even without tracks it provides exceptional grip under critical forestry conditions. With improved heavier nylon steel belted construction and reinforced hexagonal bead technology ,643 Forestar III ensures excellent puncture resistance, high load carrying capacity and prevents rim slippage. The unique tread pattern with wider shoulder lugs and horizontal grooves enhances track compatibility and overall lateral stability. Excellent self-cleaning , superior grip and resilient construction makes 643 Forestar III the perfect solution for all your forestry needs.

Forwarder & Harvester - 750/55-26.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
								Forestry Use	Road Service			
		SW mm	OD mm						Static kmph	20 kmph	30 kmph	40 kmph
750/55-26.5	AG24.00 X 26.5	750	1490	689	4565	24 182A8 182A2	3.5	6200	16740	7626	6634	6200
							4	6700	18090	8241	7169	6700
							4.5	7180	19386	8831	7683	7180
							5	7640	20628	9397	8175	7640
							5.5	8080	21816	9938	8646	8080
							6	8500	22950	10455	9095	8500

\*LT-Low Torque(Forwarder Application) \*HT-High Torque(Skidder Application) At stationery service inflation pressure must be increased by 0.3Bar Maximum  
Inflation pressure for Tracks - 6Bar or 87psi

