



ALLIANCE  
MATERIAL HANDLING

TRA: **IND-3**  
Speed Rating: **A2**

Alliance 775 is specially engineered for heavy duty forklifts and empty container handlers. It has a unique tread design that ensures long life and superior stability while carrying high loads for operations on abrasive surfaces. The strong casing in its construction provides enhanced durability and smooth working in high stress operations while resisting separations between plies as well as between the tread and the casing. There is lower heat build-up leading to reduced chances of failure due to the presence of heat & abrasion resistant compound.

ECH and Heavy Duty Forklift - 12.00-24

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load													
								Speed													
		Load wheel						Steer wheel													
SW mm	OD mm	5 kmph	10 kmph	15 kmph	25 kmph	NaN kmph	Static kmph	20 kmph	5 kmph	10 kmph	15 kmph	25 kmph	NaN kmph	Static kmph	20 kmph						
12.00-24	8.50A—24	315	1245	585	3808	20	10	10010	9320	8970	8630	11040	12420	8760	8010	7460	7010	6900	8830	9940	7180
						A2															

E-Marking Number:  
Tolerance range: +-2% for OD and SW

