



ALLIANCE
EARTHMOVER &
MINING

TRA: E-2/L-2/G-2
Speed Rating: B

Alliance 600 is a modern wide base, all steel radial tire for all types of earthmoving equipments. Its unique tread design and sophisticated construction ensure superior performance coupled with smoother rides and higher productivity

LOADER DOZER - 15.5R25 L2

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Off-the road			
		Static kmph	5 kmph					10 kmph	25 kmph		
15.5R25 L2	12.00/1.3	391	1274	576	3760	* 169A2	3.5	8020	5660	5010	4260
							4	8660	6110	5410	4600
							4.5	9280	6550	5800	4930
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		Static kmph	5 kmph					10 kmph	25 kmph		
15.5R25 L2	12.00/1.3	391	1274	576	3760	* 169A2	4.2	9020	7260	6760	6260
							4.8	9740	7840	7300	6760
							5.4	10440	8410	7830	7250

Speed:10km/h (5mph); Distance:up to 76km (250 miles) - one way

