



ALLIANCE
EARTHMOVER &
MINING

TRA: **E-3/G-3/L-3**
Speed Rating: **B**

Alliance 650 has a well proven tread pattern that enables its use for a wide range of applications on different kinds of mobile construction equipments. Its all steel construction ensures higher productivity with lower downtime.

LOADER DOZER - 15.5R25 L-3/E3

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Off-the road			
		Static kmph	5 kmph					10 kmph	25 kmph		
15.5R25 L-3/E3	12.00/1.3	395	1277	563	3858	** 176A2	2.5	6980	4930	4360	3710
							3	7760	5480	4850	4120
							4	9180	6490	5740	4880
							5	10460	7390	6540	5560
							5.75	11360	8020	7100	6040
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		Static kmph	5 kmph					10 kmph	25 kmph		
15.5R25 L-3/E3	12.00/1.3	395	1277	563	3858	** 176A2	3	7850	6320	5890	5450
							3.6	8730	7030	6550	6060
							4.8	10330	8320	7750	7180
							6	11770	9480	8830	8180
							6.9	12780	10300	9590	8880

Grader application

