

**ALLIANCE  
AGRICULTURE**

TRA:  
Speed Rating: **D**

Alliance 590 is a heavy duty radial flotation tire designed specifically to suit the needs of agriculture and construction applications. A robust steel belted construction with non-directional tread design and superior cut and chip resistant compound enables it to handle heavy Loads and operate both in farms as well as on/off road applications.

**Agri Transport - 600/55R26.5**



Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
								Speed								
		Mixed Application														
		Static kmph	10 kmph					20 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph	70 kmph		
600/55R26.5	AG20.00 X 26.5	611	1333	612	4071	173D	1.2	5014	3924	3597	3292	2965	2638	2333	2180	1984
							1.6	6095	4770	4373	4002	3604	3207	2836	2650	2412
							2.4	7705	6030	5528	5059	4556	4054	3585	3350	3049
							3.2	9775	7650	7013	6418	5780	5143	4548	4250	3868
							4	11845	9270	8498	7777	7004	6232	5511	5150	4687
							5	13340	10440	9570	8758	7888	7018	6206	5800	5278
							6	14950	11700	10725	9815	8840	7865	6955	6500	5915
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
								Speed								
		Mixed Application														
		Static kmph	10 kmph					20 kmph	30 kmph	40 kmph	50 kmph	65 kmph	70 kmph			
600/55R26.5	AG20.00 X 26.5	611	1333	603	4004	165D	0.8	3910	3060	2810	2570	2310	2060	1700	1550	
							1.2	5010	3920	3600	3290	2960	2640	2180	1980	
							1.6	6100	4770	4370	4000	3600	3210	2650	2410	
							2	6670	5220	4790	4380	3940	3510	2900	2640	
							2.4	7710	6030	5530	5060	4560	4050	3350	3050	
							2.8	8910	6980	6390	5850	5270	4690	3875	3530	
							3.2	9780	7650	7010	6420	5780	5140	4250	3870	
							3.6	10640	8330	7630	6980	6290	5600	4625	4210	
4	11850	9270	8500	7780	7000	6230	5150	4690								
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
								Speed								
		Mixed Application														
		Static kmph	10 kmph					20 kmph	30 kmph	40 kmph	50 kmph	65 kmph	70 kmph			
600/55R26.5	AG20.00 X 26.5	611	1333	613	4068	178D	1.2	5010	3920	3600	3290	2960	2640	2180	1980	
							1.6	6100	4770	4370	4000	3600	3210	2650	2410	
							2	6670	5220	4790	4380	3940	3510	2900	2640	
							2.4	7710	6030	5530	5060	4560	4050	3350	3050	
							2.8	8910	6980	6390	5850	5270	4690	3875	3530	
							3.2	9780	7650	7010	6420	5780	5140	4250	3870	
							3.6	10640	8330	7630	6980	6290	5600	4625	4210	
							4	11850	9270	8500	7780	7000	6230	5150	4690	
							5	13340	10440	9570	8760	7890	7020	5800	5280	
							6	14950	11700	10730	9820	8840	7870	6500	5920	
7	17250	13500	12380	11330	10200	9080	7500	6830								