



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **A8**

FarmPro 90 is engineered with a multi angle lug design with steep angles at the center that enables smooth ride along with self cleaning characteristics. The shallow angle at shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead to bead distance to facilitate perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall

TRACTOR - 380/90R46

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
		Non cyclic operation												
									Static mph	6 mph	9 mph	16 mph	19 mph	25 mph
380/90R46(14.9R46)	W12 X 46 W11 X 46 W13 X 46	15.0	73.0	34.1	220.1	165A8 165B	12	9130	5950	5310	4410	4260	3970	3970
							23	14200	9260	8270	6860	6610	6170	6170
							35	16490	10760	9610	7960	7670	7170	7170
							46	19640	12810	11440	9480	9150	8540	8540
							58	22180	14460	12920	10710	10320	9650	9650
							70	26130	17040	15210	12610	12150	11350	11350

Size	Rim		Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
									Speed	
			Cyclic operation							
	6 mph	9 mph								
380/90R46(14.9R46)	W12 X 46 W11 X 46 W13 X 46		15.0	73.0	34.1	220.1	165A8 165B	15	3060{hlc}	2790{hlc}
								29	10490	9570
								44	12190	11110
								58	14530	13250
								73	16400	14950
								87	19310	17590

*Alliance allows for free rolling application:Load capacity to be increased by 20%,after increasing the inflation pressure by 20%

