



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: **R-3**
Speed Rating: **A8**

The Alliance 329 is a diamond tread design tire built with a strong nylon construction. Its wide and extended tread protects shoulders and sidewalls against cutting and side snagging. The special cut and chip resistant compound ,heat resistant compound and the tires strong nylon construction provide long life to the tire.

TRACTOR - 14.9-24

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Field operation			Not high and sustained torque; Road transport					
								High Tor	Low Torque							
		SW inch	OD inch					6 mph	6 mph	12 mph	Static mph	6 mph	16 mph	19 mph	25 mph	31 mph
14.9-24	W13 W12	15.5	48.9	22.4	145.6	6PR	15	3020	3950	3400	6480	4230	3130	3020	2820	2560
						123A8	17	3350	4390	3750	7210	4700	3480	3350	3130	2840
							20	3660	4780	4100	7870	5140	3790	3660	3420	3110
						8PR	22	3810	5000	4280	8220	5360	3970	3810	3570	3240
						128A8	23	3970	5180	4450	8510	5560	4100	3970	3700	3370
							26	4260	5560	4760	9130	5950	4410	4260	3970	3620

Recommended rim in red (Bold)

