



ALLIANCE  
CONSTRUCTION &  
INDUSTRIAL

TRA: R-3  
Speed Rating: A8

The Alliance 330 Drive Wheel is a multi-purpose tire designed to provide high load capacity, significant traction and smooth ride comfort. It is suitable for on-the-road, design, and ozone resistant compounds provide long tread life. industrial and road construction equipment. The strong nylon construction, rugged design, and ozone resistant compounds provide long tread life.

TRACTOR HEAVY DUTY - 23.1-26

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
		SW inch	OD inch					Drive wheel				Free rolling				
								6 mph	16 mph	25 mph	31 mph	Static mph	6 mph	16 mph	25 mph	31 mph
23.1-26	DW20	23.1	62.2	27.4	181.1	10PR	17	10010	8490	8000	7280	20280	11020	9350	8820	8030
						158A8	19	10890	9240	8710	7920	22000	11970	10140	9570	8710
							20	11710	9940	9370	8530	23700	12880	10940	10310	9370
						12PR	22	12150	10300	9720	8840	24650	13400	11350	10710	9740
						162A8	23	12630	10690	10100	9190	25550	13890	11770	11110	10120
							25	13100	11110	10470	9520	26500	14400	12210	11520	10470
						16PR	28	13800	11710	11050	10050	27930	15190	12880	12150	11050
						168A8	30	14640	12410	11710	10650	29610	16090	13650	12880	11710
							33	15430	13100	12350	11240	31240	16980	14400	13580	12370
						18PR	35	15790	13380	12630	11490	31950	17370	14730	13890	12630
						170A8	36	16160	13690	12920	11750	32720	17770	15080	14220	12940
							38	16540	14020	13230	12040	33470	18190	15430	14550	13250

The Size 23.1-26-12PR is no longer active for production

