



ALLIANCE
AGRICULTURE

TRA: F-2
Speed Rating: A8

Alliance 313 tire is a multipurpose low-section steering wheel tire for heavy duty tractors. It provides high mileage on road and industrial applications. It has a strong nylon construction and uses high grade compounds which guarantee long tire life.

TRACTOR - 14L-16.1SL

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
		SW inch	OD inch					Speed						
								6 mph	9 mph	12 mph	16 mph	19 mph	22 mph	25 mph
14L-16.1SL	W11C	13.6	38.8	17.7	115.4	6PR	22	4300	3700	3330	2840	2470	2230	1980
						117A6 109A8	25	4610	3970	3570	3040	2650	2380	2120
							28	4920	4260	3810	3260	2830	2560	2270
						8PR	29	5230	4500	4060	3440	3000	2690	2400
						123A6 116A8	32	5510	4760	4280	3660	3180	2870	2540
							36	5950	5140	4610	3920	3420	3090	2730
						10PR	38	6170	5340	4780	4080	3550	3200	2840
						127A6 120A8	39	6350	5470	4920	4190	3640	3290	2910
							44	6700	5800	5200	4430	3860	3480	3090

Highlighted column indicates 1) 6PR and above with a 25% increase in inflation pressure 2) In case where front-end loader is fitted on the tractor, =100% applies.

