



ALLIANCE
EARTHMOVER &
MINING

TRA: **E-3/G-3/L-3**
Speed Rating: **B**

Alliance 690 is a modern wide-base, all-steel radial tire for all types of earthmoving equipment. Its unique tread design and sophisticated construction enable superior performance and high mileage coupled with smoother rides. The all-steel construction ensures low downtime and higher productivity.

LOADER DOZER - 17.5R25 L-3/E3

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Off-the road			
		Static mph	3 mph					6 mph	16 mph		
17.5R25 L-3/E3	14.00/1.5	18.8	53.0	24.4	157.2	** 182A2	44	20500	14480	12810	10890
							62	25110	17750	15700	13340
							65	25970	18340	16230	13800
							83	29980	21190	18740	15940
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		Static mph	3 mph					6 mph	16 mph		
17.5R25 L-3/E3	14.00/1.5	18.8	53.0	24.4	157.2	** 182A2	52	23060	18560	17280	16010
							74	28260	22750	21190	19620
							78	29210	23520	21910	20280
							100	33730	27180	25310	23440

Speed:10 Km/h (5 mph); Distance:up to 76 m (250 feet) - one way

