



ALLIANCE
AGRICULTURE

TRA:
Speed Rating: **D**

The 551 MULTIUSE PROFESSIONAL is specially designed for tractors and agro-industrial machines toiling on roads. Unique tread design with sipes provide superior grip in dry, wet and snow conditions and ensure excellent riding experience. Its special compound formulation assures smooth functioning even in extreme low temperatures . The robust steel belted construction guarantees excellent durability round the year.

TRACTOR - 440/80R28

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Constant Load							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	43 mph
440/80R28	DW14X28	17.0	55.7	25.5	167.6	151D 156A8	12	9310	5080	4300	4230	4060	3810	3530	3210
							17	11640	6350	5380	5290	5070	4760	4410	4010
							23	14550	7940	6720	6610	6340	5950	5510	5020
							29	15860	8650	7330	7210	6910	6490	6010	5470
							35	16880	9210	7800	7670	7350	6910	6390	5820
							41	18330	10000	8470	8330	7990	7500	6950	6320
							46	20080	10950	9280	9130	8820	8210	7610	6920

