



ALLIANCE
AGRICULTURE

TRA: I-3
Speed Rating: A8

Alliance 380 Implement Flotation tire provides full soil protection and flotation tire characteristics in field. The tires high-speed steel belted radial flotation construction, combined with specific casings construction and special rubber compound enables it to run at high speed on road. Deep non-directional lug type pattern enables high mobility in field including significant traction ability as well as comfortable smooth movement on road. Heavy duty tires are best suited for tough applications compared to the standard range.

IMPLEMENT - 650/60R26.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Mixed application							
		SW mm	OD mm					Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph
650/60R26.5	AG20.00	660	1450	655	4432	173D	0.8	5840	4570	4010	3840	3450	3070	2720	2540
							1.5	8440	6610	5800	5540	4990	4440	3930	3670
							1.7	9090	7110	6240	5960	5370	4780	4230	3950
							2	9980	7810	6860	6550	5900	5250	4640	4340
							2.5	11360	8890	7810	7460	6720	5980	5290	4940
							3.5	13820	10820	9500	9080	8170	7270	6430	6010
							4	14950	11700	10270	9820	8840	7870	6960	6500

