



ALLIANCE
AGRICULTURE

TRA: I-2
Speed Rating: D

Alliance 390 Heavy Duty steel belted flotation radial Implement tires belong to the Agri-Transport series combining the best of flotation characteristics with the best of radial construction characteristics to provide excellent performance both on and off road. The tires can be used for multiple machines in on/off-the-road applications. MPT tires can drive upto 100 km/h and are best suited for tough applications compared to the standard range.

HEAVY DUTY FLOTATION - 560/60R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Mixed Application							
		SW mm	OD mm					Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph
560/60R22.5	AG16.00	565	1260	569	3865	169D	0.8	4720	3690	3240	3100	2790	2480	2190	2050
							1	5360	4190	3680	3520	3170	2820	2490	2330
							1.5	6810	5330	4680	4470	4030	3580	3170	2960
							2	8050	6300	5530	5290	4760	4240	3750	3500
							2.5	9180	7180	6300	6020	5430	4830	4270	3990
							3	10210	7990	7020	6700	6040	5370	4750	4440
							3.5	11180	8750	7680	7340	6610	5880	5200	4860
							4	12100	9470	8310	7940	7150	6360	5630	5260
							4.5	12970	10150	8910	8520	7670	6820	6030	5640
							5	13160	10300	9040	8640	7780	6920	6120	5720
							6	13340	10440	9160	8760	7890	7020	6210	5800

