



ALLIANCE  
EARTHMOVER &  
MINING

TRA: G-2/L-2  
Speed Rating: B

Alliance 308 is a tire designed for rugged service on front-end loaders. Husky tread bars are sized and angled for maximum traction and specially contoured to resist tearing and chipping. The overlapping lugs ensure smooth rolling on any type of surface and the spacing between lugs provides self-cleaning properties. It is built with ozone and weather-resistant compounds and has a strong nylon construction.

LOADER DOZER - 15.5-25 L2,G2

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Off-the road			
		SW mm	OD mm					Static kmph	5 kmph	10 kmph	25 kmph
15.5-25 L2,G2	12SDC	394	1277	564	3720	8PR	1.75	5520	3900	3450	2930
						158A2	2	5970	4210	3730	3170
							2.25	6400	4520	4000	3400
							2.5	6800	4800	4250	3610
						10PR	2.75	7070	4990	4420	3760
						163A2	3	7440	5250	4650	3950
							3.25	7800	5510	4875	4140
						12PR	3.5	8290	5850	5180	4140
						168A2	3.75	8620	6090	5390	4310
							4	8960	6330	5600	4480
						14PR	4.25	9220	6510	5760	4900
						171A2	4.5	9540	6730	5960	5070
							4.75	9840	6950	6150	5230

For the above size 8PR,10PR and 14Pr is no longer active for production

