



ALLIANCE  
AGRICULTURE  
  
TRA: I-3  
Speed Rating: C

Alliance 328 HS (High Speed Flotation I-328) is designed with good self-cleaning characteristics, which is suitable for on and off-the-road agricultural service on trailers and implements. The high load capacity and low inflation pressure of the tire results in high degree of agricultural soil protection, as well as low rolling resistance on both, on and off-road uses. The tire is available in heavy and regular duty versions of flotation tires. Its strong nylon construction and compounds ensure long life

IMPLEMENT - 500/50R17

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Free rolling							
		SW mm	OD mm					Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph
500/50R17	16	494	960	425	2867	145D	1	2970	2320	2040	1950	1750	1560	1380	1290
							1.5	3770	2950	2590	2480	2230	1980	1750	1640
							2	4440	3470	3050	2910	2620	2340	2070	1930
							2.5	5060	3960	3480	3320	2990	2660	2350	2200
							3.2	5870	4590	4030	3850	3470	3090	2730	2550
							3.6	6280	4910	4310	4120	3710	3300	2920	2730
							4	6670	5220	4580	4380	3940	3510	3100	2900

For stationary service (0 km/h) and speed upto 10km/h inflation pressure must be increased by 20% Overall width(+/- 2%) Overall Diameter(+/-1.5%) Static Radius(+/-2%) Circumference(+/-2.5%)

