



GALAXY
AGRICULTURE

TRA: **R-1**
Speed Rating: **A6**

The Galaxy Agri-Trac II has a modern, curved 45 degree lug design for both smooth riding on the road, and excellent traction in all field conditions. Its special stepped surfaces between lugs facilitate cleaning in very muddy conditions. The wide nose bar provides extra life on hard surfaces/roading. The Agri Trac II has been reinforced with a wear resistant compound to give it long wear capabilities. The Agri Trac II has been selected as an OEM fitment tire by leading tractor manufacturers.

TRACTOR - 18.4-30

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
		Tractor Applications													
										Static kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph
18.4-30	W16L X 30 DW16A X 30 W15L X 30 DW15A X 30	467	1550	692	4567	8	0.8	4210	2560	2380	2200	1960	1830	1740	1650
						139A6 135A8	1.2	5340	3250	3020	2780	2480	2320	2200	2090
							1.3	5590	3400	3160	2920	2600	2430	2310	2190
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
		Tractor													
										Static kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph
18.4-30	W16L X 30 DW16A X 30	467	1552	709	4700	16	0.8	4140	2520	2340	2160	1930	1800	1710	1590
							1.6	6210	3780	3510	3240	2890	2700	2560	2390
						157A6 153	2.4	7870	4790	4450	4100	3660	3420	3240	3030
							3	8970	5460	5070	4680	4170	3900	3690	3460
							3.3	9490	5780	5360	4950	4410	4125	3920	3650

