



https://yokohama-atg.com Generated on: 18 May, 2024



GALAXY **AGRICULTURE**

TRA: Speed Rating: **A8** The Galaxy Super Soil Softee is designed for use in spreading liquid fertilizers. The frame provides very low footprint pressure. It is ideal for machinery and equipment used in wet soil conditions. Radial construction provides superior cut and puncture resistance.

TRACTOR - 850/50R32IMP

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
								Speed									
								Drive wheel				Free Rolling					
		SW mm	OD mm					Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	Static kmph	10 kmph	25 kmph	30 kmph	40 kmph
850/50R32IMP	DH27 X 32	850	1670	748	5087	192A8⊖• 180A8⊖	0.8	7070	4310	3660	3440	3075	7220	6130	5210	4900	4375
							1.6	11210	6830	5800	5460	4875	11390	9660	8210	7730	6900
							2.4	14950	9100	7740	7280	6500	15260	12950	11010	10360	9250
							3.3	18400	11200	9520	8960	8000	18480	15680	13330	12540	11200

