



ALLIANCE  
EARTHMOVER &  
MINING

TRA: **E-3/G-3/L-3**  
Speed Rating: **B**

Alliance 690 is a modern wide-base, all-steel radial tire for all types of earthmoving equipment. Its unique tread design and sophisticated construction enable superior performance and high mileage coupled with smoother rides. The all-steel construction ensures low downtime and higher productivity.

LOADER DOZER - 17.5R25 L-3/E3

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Off-the road			
		Static kmph	5 kmph					10 kmph	25 kmph		
17.5R25 L-3/E3	14.00/1.5	477	1345	619	3994	** 182A2	3	9300	6570	5810	4940
							4.25	11390	8050	7120	6050
							4.5	11780	8320	7360	6260
							5.75	13600	9610	8500	7230
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		Static kmph	5 kmph					10 kmph	25 kmph		
17.5R25 L-3/E3	14.00/1.5	477	1345	619	3994	** 182A2	3.6	10460	8420	7840	7260
							5.1	12820	10320	9610	8900
							5.4	13250	10670	9940	9200
							6.9	15300	12330	11480	10630

Speed:10 Km/h (5 mph); Distance:up to 76 m (250 feet) - one way

