



ALLIANCE
EARTHMOVER &
MINING

TRA: E-3/L-3/G-3
Speed Rating: B

Alliance 310 pattern is constructed for heavy-duty jobs. The tough tread design ensures high mileage even on the most abrasive surfaces. This is a directional tire built with weather and ozone-resistant compounds. Its nylon construction gives it long life.

TRANSPORT - 16.00-25 E-3

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		SW mm	OD mm					Speed								
								15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph
16.00-25 E-3	11.25	432	1493	686	4460	24PR	4	6080	5970	5860	5760	5650	5590	5540	5430	5270
						170B	4.25	6290	6180	6070	5960	5840	5790	5730	5620	5450
							4.5	6510	6390	6270	6160	6040	5980	5930	5810	5640
						4.75	6720	6600	6480	6360	6240	6180	6120	6000	5820	
						28PR	5	6910	6790	6660	6540	6420	6360	6290	6170	5980
							5.25	7110	6990	6860	6730	6600	6540	6480	6350	6160
						174B	5.5	7310	7180	7050	6920	6790	6730	6660	6530	6330
							5.75	7500	7370	7240	7100	6970	6900	6830	6700	6500
						32PR	6	7810	7670	7530	7390	7250	7180	7110	6970	6760
						177B	6.25	7990	7840	7700	7560	7420	7340	7270	7130	6920
6.5	8180	8030	7880	7740	7590		7520	7450	7300	7080						

Note: For above mentioned size 24 PR is no longer active for production.

