



ALLIANCE
AGRICULTURE

TRA:
Speed Rating: **F**

392 is an all steel tire with an F speed rating for high speed agri-transport operations. High load carrying capacity, protection against cuts & punctures, low soil compaction and low rolling resistance are some of its key features. It is suitable for heavy duty applications. Its unique tread design ensures high traction in all terrains. It is suitable for sandy and soft soil operations.

Agri Transport - 24R20.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
								Speed									
								MIXED APPLICATION									
		SW mm	OD mm					Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph	70 kmph	80 kmph
24R20.5	18.00X20.5	600	1372	620	4210	176F	1.2	6900	4968	3726	3450	3174	3091	3036	2964	2898	2760
							1.6	8175	5886	4415	4088	3761	3662	3597	3512	3434	3270
							2.4	10375	7470	5603	5188	4773	4648	4565	4457	4358	4150
							3.2	12275	8838	6629	6138	5647	5499	5401	5273	5156	4910
							4	14000	10080	7560	7000	6440	6272	6160	6014	5880	5600
							6	17750	12780	9585	8875	8165	7952	7810	7625	7455	7100

