



ALLIANCE  
AGRICULTURE

TRA:  
Speed Rating: **D**

The 551 MULTIUSE PROFESSIONAL is specially designed for tractors and agro-industrial machines toiling on roads. Unique tread design with sipes provide superior grip in dry, wet and snow conditions and ensure excellent riding experience. Its special compound formulation assures smooth functioning even in extreme low temperatures . The robust steel belted construction guarantees excellent durability round the year.

TRACTOR - 440/80R28

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Constant Load							
		SW mm	OD mm					Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	60 kmph	70 kmph
440/80R28	DW14X28	432	1416	648	4258	151D 156A8	0.8	4224	2304	1952	1920	1840	1728	1600	1456
							1.2	5280	2880	2440	2400	2300	2160	2000	1820
							1.6	6600	3600	3050	3000	2875	2700	2500	2275
							2	7194	3924	3325	3270	3134	2943	2725	2480
							2.4	7656	4176	3538	3480	3335	3132	2900	2639
							2.8	8316	4536	3843	3780	3623	3402	3150	2867
							3.2	9108	4968	4209	4140	4000	3726	3450	3140

