



GALAXY
EARTHMOVER &
MINING

TRA: **E-4/L-4**
Speed Rating: **B**

HTSR 400 is specially built for dump trucks that face extreme environments while hauling heavy loads. High tread depth ensures consistent traction and greater cut resistance making it the more productive choice. The presence of special compound ensures minimum heat build-up while performing longer runs. Superior cut & chip protection with optimized belt design provides excellent durability resulting in reduced downtime.

Articulated Dump Trucks - 29.5R25

| Size | Pattern | Rim | Unloaded Dimension | | Static Loaded Radius mm | Static Loaded Width mm | Rolling Circumference mm | NSD mm | TKPH/ TMPH | Load Index Speed Symbols | MAX SPEED | TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES | | | | | | | | | | | |
|---------|---------|--------------|--------------------|-------|-------------------------|------------------------|--------------------------|--------|------------|--------------------------|-----------|--|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | | OD mm | SW mm | | | | | | | | Star Mark | | | | | | | | | | ** | |
| | | | | | | | | | | | | KPA | 275 | 300 | 325 | 350 | 375 | 400 | 425 | 450 | 475 | 500 | 525 |
| 29.5R25 | HTSR400 | 25.00/3.5-25 | 1890 | 765 | 852.2 | 0 | 5611 | 59 | 0 | 200B | 50 KMPH | Kg | 8500 | 9250 | 9750 | 10300 | 10900 | 11500 | 11800 | 12500 | 12850 | 13600 | 14000 |

E-Marking Number:

