



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **A8**

The Alliance FarmPRO 70 Series Radial is a highly versatile range that represents the family of modern agricultural radial tires. The multi-angle lug design with steep angles at the center enables a smooth ride, along with self-clearing characteristics. In addition, the shallow angle at the shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead-to-bead distance to facilitate a perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall, which enhances the tire's visual appeal

TRACTOR - 320/70R28

| Size | Rim | Unloaded Dimension | | Loaded Static radius inch | Rolling Circumference inch | Load Index PR Symbols | Inflation Pressure psi | Recommended Load | | | | | | |
|-----------|----------|---------------------|-------|---------------------------|----------------------------|-----------------------|------------------------|------------------|--------|--------|--------|--------|------|------|
| | | | | | | | | Speed | | | | | | |
| | | Tractor application | | | | | | | | | | | | |
| | | Static mph | 6 mph | | | | | 12 mph | 16 mph | 19 mph | 25 mph | 31 mph | | |
| 320/70R28 | W10 X 28 | 12.6 | 46.8 | 21.5 | 139.8 | 119A8 119B | 12 | 4440 | 2900 | 2370 | 2140 | 2060 | 1930 | 1930 |
| | | | | | | | 17 | 5680 | 3700 | 3040 | 2740 | 2640 | 2470 | 2470 |
| | | | | | | | 23 | 6900 | 4500 | 3690 | 3330 | 3210 | 3000 | 3000 |

*Alliance allows for free rolling application:Load capacity to be increased by 20%,after increasingthe inflation pressure by 20%

