



ALLIANCE  
AGRICULTURE  
  
TRA: **R-1**  
Speed Rating: **D**

Agriflex+ 363 Very Improved Flexion (VF) is a tire for modern methods of field spraying. It is an optimal tire for heavy and high-speed self-propelled sprayers. The VF tire construction enables working with high tire deflection, providing up to 40% higher load-carrying capacity for the same inflation pressure as regular tires. The directional lug design, divided into separated blocks provides excellent grip on soft surfaces. The large number of blocks and high rubber-to-void tread ratio, ensure long tread life, comfort, and low rolling resistance during transport operation on hard surfaces. A large tire footprint area provides high traction, reduces fuel costs, and minimizes soil compaction. The steel belted carcass structure ensures uniform ground pressure, puncture protection, and extended tread life.

TRACTOR - VF230/95R32

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		Not high and sustained torque;Road transport													
		6 mph	9 mph					12 mph	16 mph	19 mph	25 mph	40 mph	43 mph		
VF230/95R32	W8 X 32 W7 X 32	9.2	49.2	23.0	148.2	136D	12	2490	2380	2360	2340	2320	2270	2270	2070
							17	3200	3060	3020	3000	2980	2910	2910	2650
							23	3880	3700	3660	3640	3590	3530	3530	3220
							29	4260	4060	4010	3970	3950	3860	3860	3510
							35	4610	4410	4370	4320	4280	4190	4190	3810
							41	5000	4760	4720	4670	4630	4540	4540	4120
							46	5420	5180	5140	5090	5030	4940	4940	4500
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								CYCLIC OPERATION							
		SW inch	OD inch					6 mph							
VF230/95R32	W8 X 32 W7 X 32	9.2	49.2	23.0	148.2	136D	23	3180							
							29	4080							
							35	4940							
							41	5400							
							46	5860							
							52	6350							
							58	6920							

E-Marking Number:

