



GALAXY  
EARTHMOVER &  
MINING

TRA: E-3/L-3  
Speed Rating: B

LDSR 300 is specially constructed for wheel loaders operating in the toughest environments. Transportation of heavy load demands excellent stability and robustness. Sturdy radial construction coupled with strong sidewall protector provides LDSR 300 superior strength and endurance to withstand challenging terrains. Premium tread compounds provide excellent protection against lug-tearing and chunking, helping the machine to perform efficiently without any downtime shaped tread pattern with stepped lugs ensure optimal traction and enhanced self cleaning assuring high productivity.

Articulated Dump Trucks - 17.5R25

Size	Pattern	Rim	Unloaded Dimension		Static Loaded Radius inch	Static Loaded Width inch	Rolling Circumference inch	NSD 1/32 inch	TKPH/ TMPH	Load Index Speed Symbols	MAX SPEED	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES											
												Star Mark											**
			OD inch	SW inch								Psi	40	44	47	51	54	58	62	65	69	73	76
17.5R25	LDSR 300	14.00/1.5 X 25	53.1	17.5	24.5	0	157.8	36.4	0	167B	31 MPH	lbs	7400	7850	8250	8800	9100	9650	10200	10500	11000	11400	12000

E-Marking Number:

