



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **A8**

FarmPRO 85 series of agricultural radial tires have multi angle lug design with steep angles at the center that enables smooth ride along with self cleaning characteristics. The shallow angle at shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead to bead distance to facilitate perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall.

TRACTOR - 340/85R36

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
		Tractor Application												
	Static mph	6 mph	16 mph					19 mph	25 mph	31 mph				
340/85R36(13.6R36)	W12 X 36 W11 X 36	13.9	58.7	27.1	170.7	132A8 132B	12	6350	4150	3060	2950	2760	2760	
							17	8380	5470	4030	3900	3640	3640	
							20	9130	5950	4410	4260	3970	3970	
							23	10140	6610	4890	4720	4410	4410	
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
		Tractor Application												
	6 mph	16 mph	19 mph					25 mph	31 mph	40 mph	Static mph			
340/85R36(13.6R36)	W12 X 36 W11 X 36	13.9	58.7	27.1	170.7	132D	12	4150	3260	3180	3020	2900	2760	6350
							17	5470	4320	4190	3990	3830	3640	8380
							20	5950	4710	4560	4340	4170	3970	9130
							23	6610	5230	5070	4830	4630	4410	10140

*Alliance allows for free rolling application:Load capacity to be increased by 20%,after increasing the inflation pressure by 20%

