



ALLIANCE
AGRICULTURE

TRA: I-3
Speed Rating: A8

Alliance 380 Implement Flotation tire provides full soil protection and flotation tire characteristics in field. The tires high-speed steel belted radial flotation construction, combined with specific casings construction and special rubber compound enables it to run at high speed on road. Deep non-directional lug type pattern enables high mobility in field including significant traction ability as well as comfortable smooth movement on road. Heavy duty tires are best suited for tough applications compared to the standard range.

IMPLEMENT - 650/60R26.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Mixed application							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph
650/60R26.5	AG20.00	26.0	57.1	25.8	174.5	173D	12	12880	10080	8840	8470	7610	6770	6000	5600
							22	18610	14570	12790	12210	11000	9790	8660	8090
							25	20040	15680	13760	13140	11840	10540	9330	8710
							29	22000	17220	15120	14440	13010	11570	10230	9570
							36	25040	19600	17220	16450	14820	13180	11660	10890
							51	30470	23850	20940	20020	18010	16030	14180	13250
							58	32960	25790	22640	21650	19490	17350	15340	14330

